

Scart Signal Distribution Buffer

K-6253S

K-6253S is distributing CVBS and Video(R,G,B), Audio(R,L) signal of Scart Jack of Europe type PAL TV without amplification, attenuation and distortion.



Features

- 20KHz Audio Bandwidth.
- Video Bandwidth
(250 MHz -3.0dB)
- Y/C TYPE Application possibility



Specifications

Pin Specifications

No	Name	No	Name	No	Name	No	Name	No	Name
1	Audio right out	5	Blue Gnd	9	Green Gnd	13	Red Gnd	17	Video Gnd
2	Audio right in	6	Audio left in	10	Data 2	14	Gnd	18	RGB Control Gnd
3	Audio left out	7	Blue	11	Green	15	RED	19	Video Output
4	Audio left in	8	Function S/W	12	Data1	16	RGB Control	20	Video Input

* About No.8 Pin

·0~2V: TV Mode ·5~8V: Wide screen Mode ·9.5~12V: AV Mode

* About No.16 Pin

·0~0.4V: Composite ·1~3V: RGB ·21Pin: Gnd

■ AC Mains

Frequency : 50~60 Hz
 Voltage : 90V~260V Auto Switching
 Power consumption : 20VA (max)
 Operating Humidity/ Temperature : 80% / -10°C~60°C
 Size : 60 * 370 * 170 (H * W * D)