


Analog Video Signal Distribution Buffer

K-6250



K-6250 receives Analog Video(Red,Green,Blue) and Sync signal(HS,VS) and then distribute without amplification, attenuation and distortion.

Not only trust test of high resolution CRT Monitor TFT LCD Monitor and PDP but also various area, e.g. Showroom, conference room, school, it can be applied.


Features

- 250 MHz Analog Video Bandwidth
- R,G,B,HS,VS BNC Input
- 5 Channel 15-pin D-sub Output
- Compact Size

Specifications

Input	
Input signal	R,G,B,HS,VS 1 line
Connectors	R,G,B,HS,VS BNC Connectors
output	
Video band width	250MHz (-3.0dB 75 ohm terminal)
Video output level	700mVp-p ± 20mV (75 ohm terminal)
Sync output level	3.0~3.5Vp-p
Connectors	15-pin D-sub 5 channel
Miscellaneous	
Voltage	90V ~ 260V (50 ~ 60Hz)
Power consumption	20VA(Max)
Humidity/Temperature	80% / -10 °C ~ 60 °C
Dimensions	44(H) X 307(W) X144(D)mm

K-6251



K-6251 receives Analog Video(Red,Green,Blue) and Sync signal(HS,VS) and then distribute without amplification, attenuation and distortion.

Not only trust test of high resolution CRT Monitor TFT LCD Monitor and PDP but also various area, e.g. Showroom, conference room, school, it can be applied.

Features

- 250 MHz Analog Video Bandwidth
- R,G,B,HS,VS BNC Input
- 10 Channel 15-pin D-sub Output
- Compact Size

Specifications

Input	
Input signal	R,G,B,HS,VS 1 line
Connectors	R,G,B,HS,VS BNC Connectors
output	
Video band width	250MHz (-3.0dB 75 ohm terminal)
Video output level	700mVp-p ± 20mV(75 ohm terminal)
Sync output level	3.0~3.5Vp-p
Connectors	15-pin D-sub 10 channel
Miscellaneous	
Voltage	90V ~ 260V (50 ~ 60Hz)
Power consumption	20VA(Max)
Humidity/Temperature	80% / -10 °C ~ 60 °C
Dimensions	63(H) X 307(W) X 144(D)mm