

K-705

DP/MHL 4CH 信号发生器

DP/MHL 4CH Signal Generator

产品特点

- 支持 DP V1.1a
- 支持 MHL V1.1
- 支持 HDCP
- 支持 RS-232
- 支持 Function Group

FEATURES

- DisplayPort V1.1a
- MHL V1.1
- HDCP
- RS-232C
- Function Group



Specifications

DISPLAYPORT OUTPUT	
Compliant	DisplayPort V1.1a
Pixel Rate Range	25MHz ~ 300MHz
Video Signal Type	RGB, YCbCr
Sampling Mode	4:4:4 / 4:2:2
Color Depth Trans.	6/8/10 bits per component
EDID	Read/Compare
HDCP	Support HDCP V1.1
Audio	2 Channel (R/L)
Audio Control Mode	Fix / Sweep / Mute / Swap
MHL OUTPUT	
Compliant	MHL V1.1 / HDMI V1.3a
Pixel Rate Range	Max 74.25MHz
Support HDMI Timing	480p, 720p_60Hz, 1080p_30Hz, 1080i_60Hz
Video Signal Type	RGB, YCbCr
Sampling Mode	4:4:4 / 4:2:2
Bits per Component	Deep color 8, 10, 12
EDID	Read/Compare
HDCP	Support HDCP V1.1
Audio	7.1CH
Audio Control Mode	Fix / Sweep / Mute / Swap
OTHERS	
AC Input	90 ~ 260 V auto range / 50 ~ 60 Hz auto range
Operation/Storage Temp.	+5~+40 deg.C / -20~+60 deg.C
DIMENSION / WEIGHT	
H X W X D / Weight	75 X 380 X 238(mm) / 4 Kgs

* All specifications are subject to change without any notice.